

### General Industrial Spring Driven Reels

#### Series RT

Reelcraft's Series RT is a new, lighter, spring-driven hose reel with a composite spool designed for applications that are less demanding, yet require a product that can withstand industrial use.

Model	Hose I.D.	Hose Length	Max PSI	(M)NPTF Hose Outlet	(F)NPTF Reel Inlet	Dimensions L x W x H (in.)	Weight (lbs)	Price
RT435-OLP	1/4"	35'	300	1/4"	3/8"	16 1/2 x 5 3/4 x 17 7/8	21	<b>\$147.00</b>
RT450-OLP	1/4"	50'	300	1/4"	3/8"	16 1/2 x 5 3/4 x 17 7/8	24	<b>\$177.00</b>
RT635-OLP	3/8"	35'	300	1/4"	3/8"	16 1/2 x 5 3/4 x 17 7/8	21	<b>\$166.00</b>
RT650-OLP	3/8"	50'	300	1/4"	1/2"	16 1/2 x 6 1/4 x 17 7/8	27	<b>\$214.00</b>
RT835-OLP	1/2"	35'	300	1/2"	1/2"	16 1/2 x 6 1/4 x 17 7/8	27	<b>\$225.00</b>
RT850-OLP	1/2"	50'	300	1/2"	1/2"	16 1/2 x 7 3/4 x 17 7/8	37	<b>\$287.00</b>

LOW PRESSURE AIR/WATER REELS Maximum Temperature 150° F (65° C)



Series RT  
RT650-OLP  
Patent No. 7,150,425


### Premium Industrial Spring Driven Reels

#### Series 4000, 5000 & 5005

Reelcraft's Series 4000, 5000 and 5005 reels are all steel construction and compact for a wide range of applications with critical space requirements. A full flow shaft and swivel assures maximum product delivery.

Model	Hose I.D.	Hose Length	Max PSI	(M)NPTF Hose Outlet	(F)NPTF Reel Inlet	Dimensions L x W x H (in.)	Weight (lbs)	Price
4425 OLP	1/4"	25'	300	1/4"	3/8"	12 5/8 x 5 3/8 x 12 7/8	19	<b>\$177.00</b>
4435 OLP	1/4"	35'	300	1/4"	3/8"	12 5/8 x 5 3/8 x 12 7/8	19	<b>\$189.00</b>
5450 OLP	1/4"	50'	300	1/4"	3/8"	13 1/2 x 6 x 14 1/2	26	<b>\$248.00</b>
4625 OLP	3/8"	25'	300	1/4"	3/8"	12 5/8 x 5 3/8 x 12 7/8	20	<b>\$196.00</b>
5635 OLP	3/8"	35'	300	1/4"	3/8"	13 1/2 x 6 x 14 1/2	25	<b>\$236.00</b>
5650 OLP	3/8"	50'	300	1/4"	3/8"	16 1/2 x 6 x 17 1/2	36	<b>\$285.00</b>
A5825 OLP	1/2"	25'	300	1/2"	3/8"	13 1/2 x 6 x 14 1/2	27	<b>\$255.00</b>
A5850 OLP	1/2"	50'	300	1/2"	3/8"	16 1/2 x 7 x 17 1/2	41	<b>\$320.00</b>

LOW PRESSURE AIR/WATER REELS Maximum Temperature 150° F (65° C)



Series 4000  
4625 OLP



Series 5005  
A5850 OLP

### General Use Hand Crank Reels

#### Series CU

Reelcraft's Series CU reels are designed for lighter-duty applications that require longer lengths of low pressure air/water hose. Hand crank with a brass swivel and brass inlet, Series CU is the product of lighter weight components and forward-thinking design.

Model	Hose I.D.	Hose Length	Max PSI	(M)NPTF Outlet	(F)NPTF Reel Inlet	Dimensions L x W x H (in.)	Weight (lbs)	Price
Light Duty Industrial Reels			Hose not included					
CU6050LN	3/8"	50'	300	3/8"	3/8"	11 x 16 3/4 x 11 1/2	10	<b>\$73.00</b>
CU6100LN	3/8"	100'	300	3/8"	3/8"	11 x 20 4/5 x 11 1/2	13	<b>\$92.00</b>



Series CU  
CU6100LN

### Spring Driven Composite Reels Series S

Reelcraft's Series S is economical, durable and lighter weight utilizing a practical combination of the latest composite materials and metals with applications including water, air and hot wash (pre-rinse).

Model	Hose I.D.	Hose Length	Max PSI	(M)NPTF Hose Outlet	(F)NPTF Reel Inlet	Dimensions L x W x H (in.)	Weight (lbs)	Price
Air & Water Reels Air hose can be used for water on these models. Working temperature 150° F (65° C).								
SGA3650 OLP	3/8"	50'	232	3/8"	3/8"	22 <sup>3</sup> / <sub>4</sub> x 9 <sup>1</sup> / <sub>2</sub> x 19	21	<b>\$214.00</b>
SGA3665 OLP	3/8"	66'	232	3/8"	3/8"	22 <sup>3</sup> / <sub>4</sub> x 9 <sup>1</sup> / <sub>2</sub> x 19	25	<b>\$233.00</b>
SGA3850 OLP	1/2"	50'	232	1/2"	1/2"	22 <sup>3</sup> / <sub>4</sub> x 9 <sup>1</sup> / <sub>2</sub> x 19	23	<b>\$222.00</b>
Water Reel Garden-style hose end. Working temperature 150° F (65° C).								
SWA3850 OLP	5/8"	50'	145	3/4" NH	1/2"	22 <sup>3</sup> / <sub>4</sub> x 9 <sup>1</sup> / <sub>2</sub> x 19	23	<b>\$222.00</b>
Hot Water Wash Reel NOTE: Working temperature 185° F (85° C). Working pressure is related to working temperature.								
SHA3850 OLP	1/2"	50'	232	1/2"	1/2"	22 <sup>3</sup> / <sub>4</sub> x 9 <sup>1</sup> / <sub>2</sub> x 19	22	<b>\$248.00</b>



### Light/Medium Duty Cord Reels

#### Series LD, LG & LH

Reelcraft's new line of light and medium duty cord reels are designed for less strenuous applications in which a capable and long-lasting reel is required. The Series LD, LG and LH cord reels help make the workplace safe by keeping long electrical cords up and out of harm's way.



Model	Cord Ending	Cord Specifications					Volts	AMPS	Weight (lbs)	Price
		AWG	# Cond.	Length	Type					
Light Duty Cord Reels										
LD2030 163 9	Triple Outlet	16	3	30'	SJTW	125	10	8	<b>\$65.00</b>	
LD2040 163 2	Fluorescent	16	3	40'	SJTW	120	0.3	11	<b>\$117.00</b>	
Medium Duty Cord Reels										
LG3050 143 9	Triple Outlet	14	3	50'	SJTW	125	13	14	<b>\$163.00</b>	
LG3050 163 8	Fluorescent	16	3	50'	SJTW	120	10	13	<b>\$183.00</b>	
LG3040 123 9	Triple Outlet	12	3	40'	SJTW	125	15	14	<b>\$174.00</b>	
Medium Duty Hand Crank Reels										
LH2080 143	4 Outlets	14	3	80'	SJTW	125	10	15	<b>\$97.00</b>	



### Power and Light Cord Reels

#### Series L4000

Reelcraft's Series L4000 power and light cord reels are easy to mount and structurally strong. The reels have a robotically welded heavy gauge steel frame that attaches to most structurally sound surfaces.



Model	Cord Ending	Cord Specifications					Volts	AMPS	Weight (lbs)	Price
		AWG	# Cond.	Length	Type					
Power Cord Reels										
L 4050 163 3	Single Receptacle	16	3	50'	SJTOW	125	13	26	<b>\$325.00</b>	
L 4545 123 3	Single Receptacle	12	3	45'	SJEOW	125	15	27	<b>\$355.00</b>	
L 4545 123 3A	Single Connector	12	3	45'	SJEOW	125	20	28	<b>\$375.00</b>	
Light Cord Reels										
L 4035 163 8	Fluorescent Light and Outlet	16	3	35'	SJTO	125	10	25	<b>\$356.00</b>	
L 4050 163 8	Fluorescent Light and Outlet	16	3	50'	SJTO	125	10	27	<b>\$374.00</b>	
L 4050 163 1	Incandescent	16	3	50'	SJTOW	125	13	27	<b>\$325.00</b>	
L 4050 162 2	Fluorescent	16	2	50'	SJTOW	125	0.3	26	<b>\$363.00</b>	

